



**Installation Details**

**Overage**

Please add a healthy overage ranging 15~20%, as shipping additional material can be expensive.

**Fastening (Exterior)**

Two ring or screw-shank headed face nails or screws per furring strip within 1" of each edge

**Substrate (Exterior)**

Rigid furring maximum 16" on-center

**Installation Layout**

Vertical or horizontal, all profiles

**Dimensions & Grades Available**

Select Grade				
SKU#	Profile	Length	Reveal	SF/pc
PA2111	6" Lap	145 11/16***	5 5/16"	5.33
PB2111	6" S3S	145 11/16"	5 11/16"	5.75
PE2111	8" Lap	145 11/16"	7 5/16"	7.33
PF2111	8" S3S	145 11/16"	7 11/16"	7.75
Premium Clear Grade				
SKU#	Profile	Length	Reveal	SF/pc
PD2111	6" Lap	145 11/16"	5 5/16"	5.33

\*\* 72", 96", 120" lengths sometimes available

**Prefinish Specifications**

Prefinish Option	1 Coat Traditional Linseed Oil
Prefinish Color	Black
Exterior Application	Yes
Interior Application	No
Back-Oiling Option	Available
2nd Coat Oil Option	Not available
Shop-Applied Fire Retardant	Available
Pressure Treated Fire Retardant	Not available



**Manufacturer**

**Nakamoto Forestry North America**

**Warehouse and Office (By Appt Only)**  
6400 SE 101st Ave Unit 2C & 3C  
Portland Oregon 97266  
Tel. (503) 512-6780

**Mailing and Billing**  
4110 SE Hawthorne Blvd. #190  
Portland Oregon 97214

**Pika-Pika with Linseed Oil BLACK (previous SKU# NM2002)**

Yakisugi "shou sugi ban" siding. Wire-brushed, textured surface, with all loose soot removed revealing a striped pattern. Suitable for exterior applications. Delivered ready to install.

**Product does not shed soot after installation**

**Copy and Paste into Appropriate CSI Division**

**SECTION 06 26 00 or 07 46 00**

**CHARRED WOOD SIDING**

**Surface & Texture**

Pika-Pika is a surface with deep wire-brushed topography of soft early wood valleys and burnt late wood ridges.

**Species**

*Cryptomeria japonica*, a monotypic genus in the Cypress family native to Japan. The Japanese name is "Sugi" (as in yakisugi and shou sugi ban), and in the West it is colloquially known as "Japanese Cedar".

**Wood Grade**

Select - JAS "Small Knot" grade allows for up to 20 tight or 10 dead knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

Premium Clear - JAS "Joko Mubushi" grade allows for up to 4 tight or 3 dead pinhole knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, no pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

**Fire Resistance**

Pika-Pika tests to ASTM E84 and UL723 Class B Flame Spread and Smoke Developed without fire retardant. Species tests to CAN/ULC S102-10 FS of 25 and SDC of 60 without fire retardant. Acceptable for Calfire WUI zone exterior applications as cladding over a 60-minute Class A wall assembly.

**Moisture Content**

Air dried then kiln dried to 11~14% MC, but may fluctuate during transport or warehousing. Please acclimate on site for two weeks prior to installation.

**1x6 Shiplap Dimensions**

- Nominal 1x6x12
- 5 5/16 inches (135mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 5.33 SF/piece

**1x6 Square Edge Dimensions**

- Nominal 1x6x12
- 5 11/16 inches (145mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 5.75 SF/piece

**1x8 Shiplap Dimensions**

- Nominal 1x8x12
- 7 5/16 inches (185mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 7.33 SF/piece

**1x8 Square Edge Dimensions**

- Nominal 1x8x12
- 7 11/16 inches (195mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 7.75 SF/piece

\*Dimensional shrinkage after manufacture is possible due to being a solid-sawn wood product.

