# NAKAMOTO FORESTRY

614



#### Installation Details Overage

Please add a healthy overage ranging 15~20%, as shipping additional material can be very expensive.

#### Fastening (Exterior)

Two ring- or screw-shank headed face nails per furring strip within 1" of each edge Substrate (Exterior) Rigid furring minimum 16"OC Fastening (Interior) Tube adhesive and pin nails Substrate (Interior) Per design specifications Installation Layout Vertical or horizontal, all profiles

#### **Dimensions & Grades Available**

	Selec	Premium Clear Grade					
6" Lap	4" S3S*	6" S3S	8" S3S	6" Lap			
*Non-standard item, limited inventory available							

Profile	SF/pc	Length	Reveal	Thickness
6" Lap	5.33	145 11/16"**	5 5/16"	9/16"
4" S3S	3.5	145 11/16"	3 1/2"	9/16"
6" S3S	5.75	145 11/16"**	5 11/16"	9/16"
8" S3S	7.75	145 11/16"	7 11/16"	9/16"

\*\* 72", 96", 120" lengths sometimes available

# Manufacturer

Nakamoto Forestry North America Warehouse and Office (By Appt Only)

6400 SE 101st Ave Unit 2C & 3C Portland Oregon 97266 Tel. (503) 512-6780

Mailing and Billing 4110 SE Hawthorne Blvd. #190 Portland Oregon 97214 Tel. (503) 512-6780





Yakisugi "shou sugi ban" siding and paneling. Wire-brushed, textured surface, with all loose soot removed revealing a striped pattern. Suitable for exterior and interior applications. Available with factory oil prefinish. Delivered ready to install.

#### Product does not shed soot after installation (except SKU# NM1919) Copy and Paste into Appropriate CSI Division

SECTION 06 26 00 CHARRED WOOD [SIDING] [&] [PANELING]

# **Prefinish Options Available**

The SKU indicates surface and prefinish combination only. Please specify SKU together with dimensional profile and wood grade when ordering.

SKU# NM1919 - UNOILED

#### 1 Coat Traditional Linseed Oil (interior & exterior)

SKU# NM2002 - BLACK SKU# NM2003 - DARK GRAY SKU# NM2004 - LIGHT GRAY SKU# NM2017 - WHITE SKU# NM1710 - NATURAL SKU# NM1724 - AMBER SKU# NM1715 - RUSTIC BROWN

#### 2 Coats Non-Toxic Polyurethane (interior only)

SKU# NM2020 - CLEAR

# NAKAMOTO FORESTRY

# Surface & Texture

Pika-Pika is a surface with deep wire-brushed topography of soft early wood valleys and burnt late wood ridges.

# Wood Grade

**Select** - JAS "Small Knot" grade allows for up to 20 tight or 10 dead knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

**Premium Clear -** JAS "Joko Mubushi" grade allows for up to 4 tight or 3 dead pinhole knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, no pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

#### Species

Cryptomeria japonica, a monotypic genus in the Cypress family native to Japan. The Japanese name is "Sugi" (as in yakisugi and shou sugi ban), and in the West it is colloquially known as "Japanese Cedar".

### **Moisture Content**

Air dried then burnt to 11~14% MC, but may fluctuate during transport or warehousing. Please acclimate on site for at least two weeks prior to installation.

## **Fire Resistance**

FRTW or shop-applied fire retardant pretreatment available to achieve CLASS A ASTM, UL, and CAN/ULC Flame Spread and Smoke Developed indices.

