



Installation Details

Overage

Please add a healthy overage ranging 15~20%, as shipping additional material can be expensive.

Fastening (Exterior)

Two ring or screw-shank headed face nails or screws per furring strip within 1" of each edge

Substrate (Exterior)

Rigid furring maximum 16" on-center

Installation Layout

Vertical or horizontal, all profiles

Dimensions & Grades Available

Select Grade				
SKU#	Profile	Length	Reveal	SF/pc
SA2411	6" Lap	145 11/16"	5 5/16"	5.33
SB2411	6" S3S	145 11/16"	5 11/16"	5.75
SE2411	8" Lap	145 11/16"	7 5/16"	7.33
SF2411	8" S3S	145 11/16"	7 11/16"	7.75

Prefinish Specifications

Prefinish Option	Exterior Grade 1 Coat Traditional Tung Oil
Prefinish Color	Black
Exterior Application	Yes
Interior Application	No
Back-Oiling Option	Not available
2nd Coat Oil Option	Not available
Shop-Applied Fire Retardant	Available
Pressure Treated Fire Retardant	Not available



Manufacturer

Nakamoto Forestry North America

Warehouse and Office (By Appt Only)
6400 SE 101st Ave Unit 2C & 3C
Portland Oregon 97266
Tel. (503) 512-6780

Mailing and Billing

4110 SE Hawthorne Blvd. #190
Portland Oregon 97214

Suyaki Exterior with Tung Oil BLACK (previous SKU# NM2014)

Yakisugi "shou sugi ban" siding. Original unbrushed charred surface, suitable for exterior applications. Leathery texture with maximum wood and color longevity, and even black color. Delivered ready to install. Exterior grade finish is very delicate and not suitable for high-traffic applications.

Coated Suyaki is a stable, clean surface that does not noticeably shed soot. Installation and weathering over decades will cause soot layer blemishes, and these are a characteristic of this very traditional product.

Copy and Paste into Appropriate CSI Division

SECTION 06 26 00 or 07 46 00

CHARRED WOOD SIDING

Surface & Texture

Suyaki is a surface with small to large crevasse patterns, variable from ¼"~1.5" wide rectangles. The soot layer is approximately 1/16" thick.

Species

Cryptomeria japonica, a monotypic genus in the Cypress family native to Japan. The Japanese name is "Sugi" (as in yakisugi and shou sugi ban), and in the West it is colloquially known as "Japanese Cedar".

Wood Grade

JAS "Small Knot" grade allows for up to 20 tight knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

Fire Resistance

Suyaki tests to ASTM E84 and UL723 CLASS A Flame Spread and Smoke Developed without fire retardant. Species tests to CAN/ULC S102-10 FS of 25 and SDC of 60 without fire retardant. Acceptable for Calfire WUI zone exterior applications as cladding over a 60-minute Class A wall assembly.

Moisture Content

Air dried then kiln dried to 11~14% MC, but may fluctuate during transport or warehousing. Please acclimate on site for two weeks prior to installation.

1x6 Shiplap Dimensions

- Nominal 1x6x12
- 5 5/16 inches (135mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 5.33 SF/piece

1x6 Square Edge Dimensions

- Nominal 1x6x12
- 5 1/16 inches (145mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 5.75 SF/piece

1x8 Shiplap Dimensions

- Nominal 1x8x12
- 7 5/16 inches (185mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 7.33 SF/piece

1x8 Square Edge Dimensions

- Nominal 1x8x12
- 7 1/16 inches (195mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 7.75 SF/piece

*Dimensional shrinkage after manufacture is possible due to being a solid-sawn wood product.

