



Installation Details

Overage

Please add a healthy overage ranging 15~20%, as shipping additional material can be expensive.

Fastening (Exterior)

Two ring or screw-shank headed face nails or screws per furring strip within 1" of each edge

Substrate (Exterior)

Rigid furring maximum 16" on-center

Installation Layout

Vertical or horizontal, all profiles

Dimensions & Grades Available

Select Grade				
Part #	Profile	Length	Reveal	SF/pc
CA2618	6" Lap	145 11/16"	5 5/16"	5.33
CB2618	6" S3S	145 11/16"	5 11/16"	5.75
CF2618	8" S3S	145 11/16"	7 1/2"	7.5
Premium Clear Grade				
Part #	Profile	Length	Reveal	SF/pc
CD2618	6" Lap	145 11/16"	5 5/16"	5.33

Prefinish Specifications

Prefinish Option	1 Coat Weathering Stain
Prefinish Color	Silver
Exterior Application	Yes
Interior Application	No
Back-Oiling Option	Available
2nd Coat Oil Option	Not available
Shop-Applied Fire Retardant	Available
Pressure Treated Fire Retardant	Available in large volume only



Manufacturer

Nakamoto Forestry North America

Warehouse and Office (By Appt Only)
6400 SE 101st Ave Unit 2C & 3C
Portland Oregon 97266
Tel. (503) 512-6780

Mailing and Billing
4110 SE Hawthorne Blvd. #190
Portland Oregon 97214

Sugi with Weathering Stain SILVER (previous SKU# NM2016)

High-grade Japanese Sugi siding and paneling. Simple sawn straight logs, graded for color and grain, then sanded. Suitable for exterior applications only. Delivered with factory stain ready to install. Substitute on projects where North American Cedar or Cypress are specified.

Dimensions and profiles matched to our yakisugi products

Copy and Paste into Appropriate CSI Division

SECTION 06 26 00 or 07 46 00

WOOD [SIDING] [&] [PANELING]

Surface & Texture

Sugi has good color variety and consistency, ranging from light tan to clay brown. These planks are simple sawn with bark side out to prevent shake (grain delamination), and have improved durability in exterior applications. Sanded to 120 grit.

Species

Cryptomeria japonica, a monotypic genus in the Cypress family native to Japan. The Japanese name is "Sugi" (as in yakisugi and shou sugi ban), and in the West it is colloquially known as "Japanese Cedar".

Wood Grade

Select - JAS "Small Knot" grade allows for up to 20 tight or 10 dead knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

Premium Clear - JAS "Joko Mubushi" grade allows for up to 4 tight or 3 dead pinhole knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, no pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

Fire Resistance

Shop-applied fire retardant pretreatment available. Species tests CAN/ULC S102-10 FS of 25 and SDC of 60 without fire retardant. Please consult with us on your specific needs.


Moisture Content

Air dried then kiln dried to 11~14% MC, but may fluctuate during transport or warehousing. Please acclimate on site for two weeks prior to installation.

Premium Clear Grade




Select Grade




1x6 Shiplap Dimensions

- Nominal 1x6x12
- 5 5/16 inches (135mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 5.33 SF/piece




1x6 Square Edge Dimensions

- Nominal 1x6x12
- 5 1/16 inches (145mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 5.75 SF/piece



1x8 Square Edge Dimensions

- Nominal 1x8x12
- 7 1/2 inches (190mm) actual reveal
- 145 11/16 inches (3700mm) actual length
- 7.5 SF/piece



*Dimensional shrinkage after manufacture is possible due to being a solid-sawn wood product.

