

Hinoki Moulder Blanks

Hinoki cypress (*Chamaecyparis obtusa*) is an aromatic and rot-resistant lumber species native to central and southern Japan. The wood's straight grain, light color, and luxe planed sheen make it an ideal aesthetic material for wall, floor, and ceiling surfaces. Our premium clear grade (without knots) hinoki moulder blanks are designed to be custom milled by your local moulder.

Copy and Paste into Appropriate CSI Division

SECTION 06 26 00 or 07 46 00

WOOD PANELING



Scan QR code for pricing, sustainability and other data


Profile	Premium Clear Grade
1 x 5 x 12 Moulder Blank	HM2000

Considerations

- Rough-sawn and dried, ready for your local moulder or millwork shop
- Ideal for saunas, interior paneling, ceilings, flooring, cabinetry; can be used for millwork glue-ups, furniture, or other applications
- Prized for its natural aromatics, rot-resistance, and blonde color
- If coated with a finish, the wood will lose its fragrant qualities
- Will develop brown flecks or marbling in exterior exposure
- Can be substituted for Port Orford Cedar in most specifications

Moulder Blank Dimensions (diagrams below are 60% actual size)

- All 145-11/16" lengths



Example profiles available from your local moulder


T&G Nickel Gap moulded from a hinoki blank



T&G



V-Match



S4S



Nickel Gap



Shiplap



Channel lap



Beveled Lap



Wood Grade

Premium Clear



Premium Clear grade allows for up to 4 tight or 3 dead pinhole knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, no face pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

Prefinish

Hinoki's durability and preservability are among the highest levels in the world. Its aesthetic beauty and resiliency make hinoki an excellent choice for both interior and exterior applications, with or without a finish applied. If coated with a finish, the wood will lose its fragrant qualities.

Prefinish Options

n/a

Prefinish Color

n/a

Exterior Application

Will develop brown flecks and marbling

Interior Application

Yes

Pressure-Treated Fire Retardant

Not available

Field Cuts

n/a

Species

Chamaecyparis obtusa, an aromatic and rot-resistant lumber species native to central and southern Japan. Hinoki wood is revered for its aromatic compounds (including alpha-terpineol and limonene) which provide an incense-like fragrance while also serving as natural defenses against insects.

Manufacturer

Nakamoto Forestry North America

Warehouse & Office (By Appt Only)

7320 NE 55th Ave.
Portland Oregon 97218
Tel. (503) 512-6780

Installation Details

Overage

Please add a healthy overage ranging 15-25%, as shipping additional material can be expensive

Fastening (Interior)

Per design specifications

Substrate (Interior)

Per design specifications

Installation Layout

Per design specifications

Fire Resistance

Please inquire with our Sales team for current certifications and listings.

Moisture Content

Air dried then kiln dried to 11-14% MC, but may fluctuate during transport or warehousing. Please acclimate in the installation location for two weeks prior to installation.

