



Pika-Pika Polyurethane Clear

Yakisugi "shou sugi ban" siding and paneling. Wire-brushed and textured surface. Most of the soot is removed, revealing a striped pattern. A clear polyurethane is applied prior to shipping. Suitable for interior applications only. Delivered ready to install.

Copy and Paste into Appropriate CSI Division SECTION 06 26 00 or 07 46 00 CHARRED WOOD PANELING



Scan QR code for pricing, sustainability and other data

Profile	Grade		
	Select	Premium Clear	Clear Vertical Grain
1 x 6 x 12 Shiplap	PA2529	PD2529	-
1 x 6 x 12 S3S Square Edge	PB2529	-	-
1 x 8 x 12 Shiplap	PE2529	-	-
1 x 8 x 12 S3S Square Edge	PF2529	-	-
1 x 2 x 12 S3S Square Edge	_	_	PG2529

Considerations

- The non-toxic interior polyurethane coating has a satin sheen.
- · Dramatically shows the opulent, natural wood grain.
- · Sort this product by tone on each wall section when installing for a more uniform appearance.
- Soot residue, caking, and erosion is unavoidable and will cause the finish to blemish, especially along board edges; this is a natural characteristic of this product.
- · To prevent blocking between boards as well as abrasion blemishes, keep boards slip-sheeted until installation.

Wood Grade Select



JAS "Small Knot" grade allows for up to 20 tight or 10 dead knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.

Premium Clear



Premium Clear grade allows for up to 4 tight or 3 dead pinhole knots per 79" (2m) board length. Unlimited combination of heartwood and sapwood, no face pith allowed. Checks allowed to 1/16" as long as plank stability, weather-resistance, and cosmetics are not adversely affected.






Profiles and Dimensions

(diagrams below are 20% actual size)

1 x 6 x 12 Shiplap

- · Charred 3 sides
- 145-11/16 (3700mm) length
- 5.33 SF/piece





1 x 6 x 12 S3S Square Edge

- · Charred 3 sides
- 145-11/16"
 (3700mm) length
- 5.75 SF/piece

1 x 8 x 12 Shiplap


- · Charred 3 sides
- 145-11/16"
 (3700mm) length
- 7.33 SF/piece






1 x 2 x 12 S3S Square Edge

- · Charred 3 sides
- 145-11/16"
 (3700mm) length
- 12 LF/piece



1 x 8 x 12 S3S Square Edge

- Charred 3 sides
- 145-11/16"
 (3700mm) length
- 7.75 SF/piece



*Dimensional shrinkage after manufacture is possible due to being a solid-sawn wood product.

Prefinish

Our non-toxic polyurethane is a clean and hard coating that protects the wood from dirt and abrasion. It can be cleaned with a moist cloth and easily touched up. It is not suitable for exterior applications or where the siding is consistently exposed to moisture.

Prefinish Options

2 coats face only

Prefinish Color

Clear

Pressure-Treated Fire Retardant

Not available

Field Cuts

Coat all field cuts and rips with touchup oil

Species

Cryptomeria japonica, a monotypic genus in the cypress family native to Japan. The Japanese name is "sugi", as in yakisugi and "shou sugi ban". In English it is colloquially called Japanese cedar.

Installation Details

For installation instructions see:

nakamotoforestry.com/installation

Overage

Please add a healthy overage ranging 15-25%, as shipping additional material can be expensive

Fastening (Interior)

Tube adhesive and pin nails

Substrate (Interior)

Per design specifications

Installation Layout

Vertical or horizontal, all profiles

Fire Resistance

Please inquire with our Sales team for current certifications and listings.

Manufacturer Nakamoto Forestry North America

Warehouse & Office (By Appt Only)

7320 NE 55th Ave. Portland Oregon 97218 Tel. (503) 512-6780





